

- Powerful motor and magnet mix up to 25L of liquid
- Large top plate surface
- Microprocessor controls

Talboys Standard and Advanced High Volume Stirrers are designed for large capacity applications. Powerful magnet and motor offer exceptional magnetic coupling force capable of stirring 25L.

Operating Features:

Low Profile Design: Takes up minimal space. Spill-resistant housing channels fluids away from internal components. Cast aluminum base offers durability and added stability.

Glass Filled Nylon Top Plate: Features a chemical resistant, reflective white top plate surface that is easy to clean.

Large Top Plate: Accommodates oversized vessels.

Microprocessor Control: Precisely regulates speed through the entire range. Stirring function, with continuous duty motor and magnet, maintains set speed even under changing load or viscosity.

Adjustment Knob: Basic speed control knob with dial markings from 1 to 10 (Standard Series).

LED Display: Touch pad controls with easy-to-read, independent LED displays for speed and time. Speed is adjustable in 10rpm increments. Timer will display elapsed time or, when programmed to user defined limit, will shut off unit when time reaches zero (Advanced Series).

Safety Features:

Audible Alarm: In timed mode, alarm will sound when time reaches zero (Advanced Series).

Speed Ramping Feature: Slowly increases speed for improved safety and enhanced coupling. Avoids splashing, improves spin bar control and provides excellent low speed control.

Operating Conditions:

Units can be run in conditions from 5 to 40°C (41 to 104°F), 20% to 80% relative humidity, non-condensing.

Applications:

Carboys, chromatography, and large volume sample stirring.

Ordering Information:

Units include a 92" (234cm) detachable, 3-wire cord and plug (230 volt units are supplied with Euro type plug). Units are also supplied with a 2.75" (7cm) PTFE coated stir bar. Additional stir bars are available on page 66. **5 year limited warranty on parts and labor.**

Optional NIST Traceable Calibration Certificate provided by Troemner's ISO/IEC 17025 accredited laboratory. Multiple data points within the speed range and time function are reported on the certificate with the associated uncertainties.



Specifications	
Speed Range	60 to 1400rpm
Speed Stability	60 to 250rpm +/-5rpm 250 to 1400rpm +/-2%
Timer (Advanced Series)	1 second to 160 hours
Maximum Capacity (H ₂ O)	25L
Maximum Vessel Diameter	10" (25cm)
Top Plate Material	Glass filled nylon
Top Plate Dimensions (L x W)	12.5 x 11" (31.8 x 27.9cm)
Overall Dimensions (L x W x H)	17 x 11 x 4" (43.2 x 27.9 x 9.7cm)
Ship Weight	14.6lbs (6.6kg)

Distributed by:
Safety Emporium
PO Box 1003
Blackwood, NJ 08012
Ph: (866) 326-5412 (toll-free)
Fax: (856) 553-6154
esales@safetyemporium.com
www.safetyemporium.com

Description	Emporium item #	Electrical (50/60 Hz)	Positions	Part Number
Standard High Volume Stirrer	23228-120	120V 1.3 amps 75 watts	1	986366
Standard High Volume Stirrer	23228-230	230V 0.65 amps 75 watts	1	986367
Advanced High Volume Stirrer	23230-120	120V 1.3 amps 75 watts	1	986368
Advanced High Volume Stirrer	23230-230	230V 0.65 amps 75 watts	1	986369
Advanced High Volume Stirrer with NIST Traceable Certificate	23230-120N	120V 1.3 amps 75 watts	1	986368-C
Advanced High Volume Stirrer with NIST Traceable Certificate	23230-230N	230V 0.65 amps 75 watts	1	986369-C