

Portable Balances							
	Scout STX	Scout SPX	Scout SJX	Navigator	Compass CX	Compass CR	
Weighing Capacity Range	120 g - 8200 g	120 g - 8200 g	64 g - 8,200 g	120 g - 20,000 g	220 g - 5,200 g	220 g - 5,200 g	
Readability Range	0.001 g - 1 g	0.001 g - 1 g	0.001 g - 1 g	0.001 g - 1 g	0.1 g - 1 g	0.1 g - 1 g	
APPLICATIONS	Weighing	●	●	●	●	●	
	Parts Counting	●	●	●	●		
	Percent Weighing	●	●	●	●		
	Check Weighing	●	●	●	●		
	Density Determination	●		●			
	Dynamic / Animal Weighing	●					
	Totalization	●	●	●			
	Mole Weighing	●					
	Display Hold	●	●	●		●	
	Gross / Net / Tare	●	●	●			
FEATURES	Control Interface	4.3" Touchscreen / Mechanical Buttons	Backlit LCD / Mechanical Buttons	Backlit LCD / Mechanical Buttons	Backlit LCD / Mechanical Buttons	Backlit LCD / Mechanical Buttons	LCD / Mechanical Buttons
	Custom Units	●	●				
	Multi-Language	●					
	Battery Power	●	●	●	●	●	●
	External Calibration	●	●	●	●	●	●
	Draftshield	●*	●*	●*	●*		
	Touchless Sensors				●		
	GLP / GMP / RTC	●					
	Weigh-Below Hook	●	●	●	○		
	NTEP / Measurement Canada			●			
COMMUNICATION PORTS	RS-232	○	○	○	○		
	USB Device	○	○	○	○		
	USB Host	○	○	○			
	Ethernet	○	○	○	○		

● Standard ●* Model Dependent ○ Optional

Distributed by:
 Safety Emporium
 PO Box 1003
 Blackwood, NJ 08012
 Ph: (866) 326-5412 toll-free
 Fax: (856) 553-6154
esupport@safetyemporium.com
www.safetyemporium.com