

MET-L-X Agent, and LITH-X Agent Dry Powder Suppressing Agents

MET-L-X Agent Application

ANSUL® MET-L-X Dry Powder Suppressing Agent may be used on sodium, potassium, sodium-potassium alloy, and magnesium fires. In addition, it will control and sometimes suppress small fires on zirconium and titanium.

MET-L-X Agent can be discharged through hose lines and is available in hand portable, wheeled, stationary, and piped system extinguishers ranging from 30 lb to 2000 lb.

MET-L-X Agent Description

MET-L-X Agent is a free-flowing dry powder composed of a salt base. Other additives, including a polymer for sealing burning metals, enhance the agent's heat caking and/or crusting performance.

MET-L-X Agent Approvals and Listings

MET-L-X Agent is listed by Underwriters Laboratories for use on sodium, potassium, sodium-potassium, and magnesium alloys. The listing includes scoop application, 30 lb hand portable extinguishers, and 150 lb and 350 lb C-Model wheeled and stationary extinguishers.

MET-L-X Agent Ordering Information

MET-L-X Agent may be purchased in steel* containers with 50 lb (22.7 kg) of agent; shipping weight is 54 lb (24.5 kg). Order Part No. 9328.

Distributed by:
Safety Emporium
PO Box 1003
Blackwood, NJ 08012
Ph: (866) 326-5412 toll-free
Fax: (856) 553-6154
esupport@safetyemporium.com
www.safetyemporium.com



009824

LITH-X Agent Application

ANSUL LITH-X Dry Powder Suppressing Agent was developed for use on lithium fires, and will also suppress magnesium, sodium, and potassium fires. LITH-X agent will contain, and in some cases completely suppress fires of zirconium, titanium, and sodium-potassium alloy.

LITH-X Agent Description

LITH-X Agent is a compound of a special graphite base with additives to render it free-flowing so that it may be used in 30 lb hand portable extinguishers, and 150 lb and 350 lb C-Model wheeled extinguishers. It does not cake or crust, but excludes air and conducts heat away from the burning mass to suppress the fire.

LITH-X Agent Ordering Information

LITH-X Agent may be purchased in steel* containers with 45 lb (20.4 kg) of agent; shipping weight is 49 lb (24.5 kg). Order Part No. 9334.

Ordering Information

For fire protection assistance, see your nearest Authorized ANSUL Distributor listed at www.ansul.com, or contact your local ANSUL Sales Representative.

*Johnson Controls may substitute steel containers with plastic containers.

Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

MET-L-X, LITH-X, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.

