SENTRY® MODEL WO2-1 PRESSURIZED WATER-TYPE **FIRE EXTINGUISHER 2.5 GALLONS (9.5 LITERS)**

Data/Specifications

FEATURES

- Meets or exceeds UL requirements
- Simple operation and maintenance
- Squeeze grip, positive on-off operation
- Brass chrome plated valve
- Waterproof stainless steel gauge
- Stainless steel shell
- Schrader valve for pressurization
- Easy service construction

DESCRIPTION

The ANSUL® Stainless Steel Water Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas. The unit features a stainless shell and chrome plated valve. The nameplate features easy to read step-by-step instructions for operating the extin-

- ▶ guisher. The Schrader valve allows for easy recharge in the field. Use of
- ▶ fresh, clean water is recommended. Reference Manual F-83163.

SPECIFICATIONS

Model No.: W02-1 **UL** Rating: 2-A

Capacity: 2.5 gallons (9.5 liters) Extinguisher Height: 25.5 in. (64.8 cm) Width: 9 in. (22.9 cm) Depth: 7 in. (17.8 cm) Range: 35 ft (10.7 meters)

Discharge Time: Approximately 50 seconds

Wall mount Bracket:

Temperature: +40 °F to 120 °F (4.5 °C to 48.9 °C)



006492

ORDERING INFORMATION

Part No.

Description

430847 SENTRY® Model W02-1 Pressurized

Water-Type Fire Extinguisher 2.5 Gallons (9.5 Liters)

Approximate Shipping Weight

9.0 lb (4.1 kg)

Distributed by: Safety Emporium PO Box 1003 Blackwood, NJ 08012 Ph: (866) 326-5412 toll-free Fax: (856) 553-6154 esupport@safetyemporium.com www.safetyemporium.com

ANSUL and SENTRY are trademarks of Tyco Fire Suppression & Building Products or its affiliates.

