

### EP08 - Corded PU Foam Ear Plugs (200 pairs)

**Collection:** Ear Plugs  
**Range:** Hearing Protection  
**Materials:** PU Foam, PVC  
**Inner Pack:** 200  
**Outer Carton:** 10

#### Product information

Disposable PU ear plugs. The tapered shape ensures a comfortable fit inside the ear canal. Corded for extra comfort and easy storage around the neck when not in use. Each pair comes inside a hygienic polybag with fitting instructions.



#### Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

#### Standards

ANSI S3.19 (NRR 32dB)  
EN 352-2 (SNR 36dB)  
EN 353-2 (SNR 33dB)



#### Features

- Disposable ear plugs made from soft PU foam
- Corded for safe keeping
- Easy to fit
- Excellent attenuation rate
- One pair per polybag for hygienic storage
- Supplied in a handy portable dispenser box
- Individually packed for vending machines
- Retail box which aids presentation for retail sales
- This product is sold in pairs
- This product is sold in inner boxes
- UKCA marked

Distributed by:  
Safety Emporium  
PO Box 1003  
Blackwood, NJ 08012  
Ph: (866) 326-5412 toll-free  
Fax: (856) 553-6154  
esupport@safetyemporium.com  
www.safetyemporium.com



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

**EP08 - Corded PU Foam Ear Plugs (200 pairs)**  
**Commodity Code: 3926909790**

**Test House**

ALIENOR CERTIFICATION (Notified Body No.: 2754)  
ZA du Sanital  
86100, France  
Cert No: 2754/1246/159/06/18/0288

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)  
SATRA Technology Park  
NN16 8SD, United Kingdom  
Cert No: AB0321/18870-01/E00-00

Michael & Associates, Inc. (Notified Body No.: )  
2766 W. College Ave Suite 1  
PA 16801, United States

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	DUN14
EP08ORR	Orange	65.0	35.0	33.0	0.8390	0.0751	5036108183852	15036108622419

Distributed by:  
Safety Emporium  
PO Box 1003  
Blackwood, NJ 08012  
Ph: (866) 326-5412 toll-free  
Fax: (856) 553-6154  
esupport@safetyemporium.com  
www.safetyemporium.com

PERFORMANCES - SOUND ATTENUATION - EN352-2:2002

<b>EP02/EP08/EP30</b>								
<b>A</b>	<b>Frequency (Hz)</b>	<b>125</b>	<b>250</b>	<b>500</b>	<b>1000</b>	<b>2000</b>	<b>4000</b>	<b>8000</b>
<b>B</b>	Means Attenuation (dB)	36.5	34.2	39.1	37.8	39.6	44.9	46.2
<b>C</b>	Standard Deviation (dB)	4.7	4.5	4.8	5.8	4.0	6.4	6.2
<b>D</b>	Assumed Protection (dB)	31.7	29.7	34.2	32.0	35.5	38.5	40.1
<b>SNR = 36 dB H = 36 dB / M = 33 dB / L = 32 dB</b>								

PERFORMANCES - SOUND ATTENUATION ANSI S.19-1974

Tested by Michael & Associates, Inc. – 400 Long Lane, PA Furnace, PA 16865, USA

<b>EP02/EP08</b>										
<b>A</b>	<b>Frequency (Hz)</b>	<b>125</b>	<b>250</b>	<b>500</b>	<b>1000</b>	<b>2000</b>	<b>3150</b>	<b>4000</b>	<b>6300</b>	<b>8000</b>
<b>B</b>	Means Attenuation (dB)	39.8	40.4	42.6	40.3	39.1	45.2	45.7	48.3	47.4
<b>C</b>	Standard Deviation (dB)	3.0	3.9	2.9	3.6	3.7	3.0	2.5	4.9	3.7
<b>NRR (Noise Reduction Rating) = 32 dB</b>										

EP08ORR

Distributed by:  
 Safety Emporium  
 PO Box 1003  
 Blackwood, NJ 08012  
 Ph: (866) 326-5412 toll-free  
 Fax: (856) 553-6154  
[esupport@safetyemporium.com](mailto:esupport@safetyemporium.com)  
[www.safetyemporium.com](http://www.safetyemporium.com)